

Toggle menu
Blue Gold Program Wiki

Navigation

- [Main page](#)
- [Recent changes](#)
- [Random page](#)
- [Help about MediaWiki](#)

Tools

- [What links here](#)
- [Related changes](#)
- [Special pages](#)
- [Permanent link](#)
- [Page information](#)

Personal tools

- [Log in](#)

personal-extra

Toggle search

Search

Random page

Views

- [View](#)
- [View source](#)
- [History](#)
- [PDF Export](#)

Actions

Summary of Section C: Water Infrastructure

From Blue Gold Program Wiki

The printable version is no longer supported and may have rendering errors. Please update your browser bookmarks and please use the default browser print function instead.

The Theory of Change for the Blue Gold Program (BGP) describes the three main sets of interventions -infrastructure, institutional and agricultural development- as the core elements of Blue Gold's approach.

Section C focuses on the improvements made through Blue Gold to the water infrastructure, specifically the polder embankments and associated structures, and the re-excavation of some of the primary drainage khals within the polder. Later sections cover water management partnerships ([Section D](#)), commercialisation of agriculture (Section E) and sustainability and inclusiveness ([Section F](#)).



Figure C.1 Simplified Blue Gold Program Theory of Change

□

Contents

- [1 Context](#)
- [2 Purpose of Polder Infrastructure](#)
 - [2.1 Safety](#)
 - [2.2 Water Management](#)
- [3 Infrastructure Investments](#)
- [4 Emergency Repairs](#)
- [5 Design Issues](#)
 - [5.1 Embankments: Climate Change](#)
 - [5.2 Structures](#)
 - [5.2.1 Life Cycle Costing](#)
 - [5.2.2 Gates](#)
 - [5.2.3 Siting of Regulators](#)
- [6 See more](#)

Context[[edit](#) | [edit source](#)]

The coastal zone in Bangladesh has a complex agro-ecology, with low lying land and huge tidal rivers. To provide protection to agricultural land from tidal and monsoonal flooding and saline water intrusion, around 1.2 million hectares are now enclosed in 139 polders, whose construction started

from the 1960s and 1970s. Now, the polders are home to about ten million people.

The tidal rivers draining the coastal zone carry flood flows during the monsoon season but are highly saline during the dry season when outflows in the tidal rivers are at their lowest. The rivers cause greatest damage to polder infrastructure during times of flood and cyclonic storms - compounded during high water spring tides - when the erosive power of the rivers can damage and even breach the polder embankments.

A breach can result in loss of life in severe cases; immediate loss of economic production - crops, fish, livestock, and businesses; damage to infrastructure - roads, utilities, homes, shops, schools; and longer-term impacts on the productivity of agricultural lands. These problems will be increasingly exacerbated by climate change and sea-level rise.

Purpose of Polder Infrastructure[\[edit](#) | [edit source](#)]

Safety[\[edit](#) | [edit source](#)]

One of the primary functions of the polder embankment is to protect the vulnerable communities who live and work in the polders from tidal floods, storm surges, river erosion and salinity through embankment strengthening, breach closing and erosion protection measures. In combination with the infrastructure improvements, disaster risk reduction (DRR) activities involving local community organisations and the concerned government departments has increased the state of preparedness of polder inhabitants to prospects of embankment breaches and overtopping and encouraged consideration of pre-emptive actions.

Water Management[\[edit](#) | [edit source](#)]

Within the polders, the re-excavation of primary canals and some major secondary canals, and rehabilitation of water management structures (sluices, outlets etc) aims to improve the overall water management and to create scope for in-polder water management (IPWM) and community-led agricultural water management (CAWM) - which is discussed in Section D Chapter 17. Where infrastructure works are complete, unobstructed flow of water is possible through the cleared main *khals*, and the rehabilitated sluices/outlets allow improved water regulation. Previously, many areas were either unable to be drained and remained inundated or suffered water shortages as their main outlets or inlets were obstructed or poorly functioning.

Photo C.1 shows one of the 186 regulators which was rehabilitated under Blue Gold. Note the agricultural area to the left of the tree-lined embankment which protects the polder area (P31-part) from high river levels, and the scale of the tidal river - the Kazibacha River. The regulator drains water into a tidal river - it is low tide so there is drainage from the polder. The high tide mark is fringed by trees and bushes.



Photo C.1 A regulator draining excess water from Polder 31-part into the Kazibacha River

Infrastructure Investments [[edit](#) | [edit source](#)]

A budget of BDT 31,420 lakh (equivalent to Euro 31.20 million) was allocated for infrastructure, in the amounts and proportions indicated in Table C.1 below.

Table C.1 Budget Allocation

Item	Allocation (September 2020)	
	BDT lakh	%age
Embankments (1, 2, 11, 12, 13)	6,544	21%
Drainage improvements (3, 14)	8,932	28%
Structures (4, 5, 6, 7, 8, 9, 10)	14,544	46%
O&M (15,16)	1,400	4%
TOTAL	31,420	

Note: See Table 11.1 for explanation of item numbers

Emergency Repairs [[edit](#) | [edit source](#)]

In the coastal zone, water infrastructure serving polder communities is expected to provide protection and facilitate water management in a particularly aggressive environment - where floods, cyclones, river erosion and accretion, salinity, tidal flows etc can cause devastating damage to embankments with the associated adverse economic consequences of large-scale flooding, or result in structures falling into disuse and unable to regulate the flow of water in and out of the polder. The resultant heavy repair and maintenance costs required to ensure the continued serviceability of the infrastructure are currently not met in full - because O&M budgets with government organisations such as BWDB are - inevitably - thinly stretched and never sufficient, local government is not mandated for this role, and community contributions fall far short of the huge sums required. This conundrum is well understood but remains unresolved, and because of these gaps, the coastal zone

remains locked in a project-driven cycle where infrastructure deterioration both precedes and follows rehabilitation.

Adequate funds for unforeseen emergencies should be made available. Under BWDB rules, funds for “emergency works” are allocated only after a breach is imminent or has occurred. At this stage, costs for repair are much more expensive because land in the vicinity of a breach is flooded, so:

- borrow pits with soils suitable for use in embankments are generally not available close to the site of a breach, so there is a cost of haulage - delivering materials to the site of the breach
- It is difficult to get machinery, equipment and materials to the site of a breach, and required labour gangs and boats
- Access by land to the site of a breach is restricted, along narrow embankments especially constructed to gain access to the breach site
- Soil from borrow pits is often saturated, and achieving acceptable level of soil compaction at high moisture content is impossible.

Pre-emptive action to strengthen vulnerable embankments before they fail is justified because costs of repair of threatened infrastructure (embankments, sluices etc) are much reduced if work is done before embankment failure; and costs in terms of human lives, and damage to crops, livestock, businesses and households can be prevented.

Emergency maintenance is a major role of BWDB in the O&M Agreement between BWDB and the polder-level WMA, and should be extended to include investments for pre-emptive works - with BWDB and WMA together agreeing a prioritized list of actions.

Design Issues[\[edit](#) | [edit source\]](#)

Embankments: Climate Change[\[edit](#) | [edit source\]](#)

Some of the direct effects of climate change on water infrastructure in the coastal zone includes:

- A rise in sea level resulting in drainage congestion and prolonged waterlogging within the polders
- More frequent cyclones and tidal surges damaging water infrastructure, properties and livelihoods as well as endangering polder communities
- Increased siltation in tidal rivers resulting in reduced drainage capacity, that impedes drainage flows from the polders.

To account for climate change effects in design, consideration was given by BWDB to harmonising Blue Gold design criteria - for raised embankment crest levels, and replacing sluices/outlets compatible with the raised embankment crest heights and with increased numbers of vents - with other projects (including WMIP, ECRRP and CEIP).

It was quickly realised that the direct costs of raising embankment crest levels and replacing regulators exceeded the Blue Gold budget allocation by many orders of magnitude. And this would be compounded by the requirement for significant land acquisition (of a strip of land 4 to 5 times the height increase for marginal and interior bunds, and significantly more for sea dykes) and compensation (eg for the relocation of assets and loss of crops).

During the first years of the project, Blue Gold intended to adopt climate change design levels including a benchmark (BM) correction partly for Polders 26, 31-part and 2. However, due to budget constraints, the 2015 Annual Review Mission recommended that the established design levels should

be adopted for the rehabilitation of all Blue Gold polders.

The limited available budget for infrastructure has meant that: (a) the choice of polders for Blue Gold has avoided those requiring high levels of investment; and (b) it has not been possible to achieve embankment crest levels which can meet the 25 year return period maximum surge height (used by CEIP-1), or to upgrade existing structures or construct new structures to suit this higher crest level, or indeed to construct the wider structures (requiring longer culvert barrels) for the higher levels of traffic on roads along the embankments.

Structures[\[edit\]](#) | [edit source](#)

Life Cycle Costing[\[edit\]](#) | [edit source](#)

After compiling all costs for an element of water infrastructure over its lifespan - including construction, operation, repair, maintenance and rehabilitation - the total can be reduced to a present value with expected return on investment (ROI). The application of life cycle costing in BWDB could achieve a balance between performance (serviceability requirements), risks and overall life cycle cost.

Gates[\[edit\]](#) | [edit source](#)

For sluices and regulators to be functional, the gates must act to prevent saline river water from entering the polder (the purpose of the flap gates on the river side), to allow excess water to be drained (by opening the vertical gates on the country side), or to allow freshwater in the rivers - during the monsoon months - to be stored in khals for subsequent use for irrigation (ie operating as a "flushing sluice" when flap gates are raised using a pulley system mounted on a lifting frame).

If the gates are of poor quality or are not properly fitted, then they quickly become inoperable, and thus the major investment in the overall structure becomes quickly un-useable. Although the cost of manufacturing and installing gates on a new regulator varies from 3.3% (1-V) to 6.5% (4-V) of the total cost of the regulator, the functionality of the structure depends on the operability of the gates. Whilst many gated structures in the coastal zone date from the 1960s, gates have a much shorter lifetime especially when they are manufactured from materials such as steel which corrode in a marine environment. There is a strong case for reviewing the design, manufacture and installation of gates to maximise their operating lifetime - taking account of the experience with life cycle costing approaches and the use of composite materials.

Siting of Regulators[\[edit\]](#) | [edit source](#)

The siltation of a river channel into which a regulator discharges, is likely to result in the regulator falling into disuse and the loss of a considerable capital investment (of up to €500k for a 4-vent structure), as well as the loss of agricultural benefits within the catchment drained by the regulator. The siting of new regulators on a river channel that will remain active for the 50+ year life of a regulator is a difficult task and relies on expertise in tidal river morphology and historical records.

In cases where regulators become blocked by sediment, internal drainage systems within the polder are re-routed to discharge water to regulators on active rivers. This is assisted by the relatively flat terrain within a polder, and the cross-linking of drainage khals. The drainage capacity of a regulator (ie the number of vents) is determined from the sluice catchment area. By including additional drainage capacity (ie more vents in a regulator) during the design process, it would be possible to reroute and dispose of drainage water from an adjacent regulator which falls into disuse because of sedimentation.

See more[[edit](#) | [edit source](#)]

Previous chapter:

[Chapter 09: The Overall Outcomes and Impacts on the Livelihoods of Coastal Communities in Blue Gold Polders](#)

[Blue Gold Lessons Learnt Wiki](#)

Section C: Water Infrastructure

Next chapter:

[Chapter 10: Coastal Infrastructure](#)

Section C: Water Infrastructure		
Chapter 10: Coastal Infrastructure	Chapter 11: Investments for Polder Safety and Water Management	Chapter 12: Survey, Design and Procurement
<ol style="list-style-type: none">Coastal ZoneBackground to Dutch-Bangladesh cooperation in the coastal region	<ol style="list-style-type: none">Polder InvestmentsRevisions to Polder Infrastructure InvestmentsInvestments by Polder and by BWDB DivisionEmergency Repairs	<ol style="list-style-type: none">Survey and design data collectionDesign
Chapter 13: Construction: Progress, Modalities and Lessons Learnt		
<ol style="list-style-type: none">Analysis of ProgressNature of WorksContractorsConstruction quality		

Executive summary: A Call for Action

<u>Section A: Background and context</u>	<u>Section B: Development Outcomes</u>	<u>Section C: Water Infrastructure</u>
<p>Summary</p> <ul style="list-style-type: none"> • Chapter 01: Overview, Purpose and Structure of Report • Chapter 02: Institutional Setting • Chapter 03: Social, Physical and Environmental Context • Chapter 04: Policy framework, history of interventions and project definition 	<p>Summary and Introduction</p> <ul style="list-style-type: none"> • Chapter 05: Outcomes and Impact from Participatory Water Management • Chapter 06: Outcomes and Impact from Agricultural Development • Chapter 07: Inclusive Development Approach: Outcomes and Impacts from Homestead Based Production • Chapter 08: The Outcomes and Impact on the Livelihoods of Women • Chapter 09: The Overall Outcomes and Impacts on the Livelihoods of Coastal Communities in Blue Gold Polders 	<p>Summary</p> <ul style="list-style-type: none"> • Chapter 10: Coastal Infrastructure • Chapter 11: Investments for Polder Safety and Water Management • Chapter 12: Survey, Design and Procurement • Chapter 13: Construction: Progress, Modalities and Lessons Learnt
<u>Section D: BGP Interventions: Participatory Water Management</u>	<u>Section E: Agricultural Development</u>	<u>Section F: Responsible Development: Inclusion and Sustainability</u>
<p>Summary</p> <ul style="list-style-type: none"> • Chapter 14: Consultation and participation in planning • Chapter 15: WMO capacity building • Chapter 16: Women's participation in Water Management • Chapter 17: In-polder water management • Chapter 18: Water Management Partnership • Chapter 19: Operationalisation of the PWM concept • Chapter 20: Way Forward 	<p>Summary</p> <ul style="list-style-type: none"> • Chapter 21: The Evolving Approach to the Commercialization of Agriculture • Chapter 22: Lessons for Agricultural Extension in the Coastal Zone • Chapter 23: Outreach and Outcomes of Commercialisation Interventions 	<p>Summary</p> <ul style="list-style-type: none"> • Chapter 24: Gender equality and women's empowerment • Chapter 25: Poverty Focus: development of homestead production • Chapter 26: Poverty focus: Labour Contracting Societies • Chapter 27: Sustainability
<u>Section G: Project Management</u>	<u>Section H: Innovation Fund</u>	<u>Files and others</u>
<p>Summary</p> <ul style="list-style-type: none"> • Chapter 28: Project Management Arrangements • Chapter 29: Technical Assistance: Context, Scope, Contractual Arrangements and External Service Contracts • Chapter 30: Evolution of TA Organisational Arrangements • Chapter 31: Capacity Building • Chapter 32: Agricultural Extension Methods and Communication • Chapter 33: Horizontal Learning • Chapter 34: Monitoring and evaluation • Chapter 35: Management Information System • Chapter 36: Environmental Due Diligence 	<p>Summary</p> <ul style="list-style-type: none"> • Chapter 37: Purpose, fund evolution and management • Chapter 38: Overview of BGIF Projects • Chapter 39: BGIF Lessons Learnt 	<ul style="list-style-type: none"> • File Library • Glossary and acronyms • Frequently Asked Questions

Blue Gold Program

A defined set of temporary activities through which facilitators seek to effect change

An area of low-lying land surrounded by an earthen embankment to prevent flooding by river or seawater, with associated structures which are provided to either drain excess rainwater within the polder or to admit freshwater to be stored in a khal for subsequent use for irrigation.

The inclusion of the (interests of) different types of people and treating them fairly and equally, considering their different roles and interests in water management

river whose flow and level are influenced by tides

Earthen dyke or bundh raised above surrounding ground level, for example so that roads or railway lines are above highest flood levels, or so that an area is empoldered to protect it from external floods and saline waters.

Disaster Risk Reduction - The Union Disaster Management Committee (UDMC) has been given the mandate to lead disaster preparedness, mitigation, emergency response and post disaster rehabilitation, by informing local people, empowering them to take practical measures to reduce risk at household and community levels and to disseminate success stories of reducing disaster risks widely among local people.

In-polder water management; term used in Blue Gold to describe water management interventions which aim to deliver excess water from the field through field drains to secondary khals and thence to primary khals for evacuation through the sluice/regulator

In-polder water management; term used in Blue Gold to describe water management interventions which aim to deliver excess water from the field through field drains to secondary khals and thence to primary khals for evacuation through the sluice/regulator

Community-led Agricultural Water Management - with DAE, Blue Gold established a network of schemes for demonstration purposes where locally-applicable annual cropping patterns are introduced along with water level control facilitated by small-scale water infrastructure, and the development of value chain skills in farmers

the principal function of a regulator or drainage sluice is to allow the drainage of water from the polder into a peripheral river when there is a differential head across the regulator (ie when the polder or country-side water level exceeds the level in the tidal river). The regulator is provided with a lift gate on the country-side (to allow freshwater to be held in the khal for irrigation during the dry season) and a flap gate on the river-side (to prevent water entry from the river channel into the polder during high tide conditions). A frame is provided on the river-side so that the flap gate can be lifted when there is freshwater in the river (during the monsoon flood season), thus allowing freshwater to be stored in the khal within the polder and used for irrigation during the dry season.

The size of the culvert is determined from the drainage area served by the structure.

Bangladesh Taka

actions taken to prevent or repair the deterioration of water management infrastructure and to keep the physical components of a water management system in such a state that they can serve their intended function.

Bangladesh Water Development Board, government agency which is responsible for surface water and groundwater management in Bangladesh, and lead implementing agency for the Blue Gold Program

Water Management Association - In Blue Gold, the polder-level representative of WMGs, and signatory to an O&M Agreement with BWDB

the south-western coastal zone is characterised by broad tidal flats and fluvio-tidal plains, lying approximately 1 metre above sea level, with drainage provided by numerous tidal creeks and channels a some major rivers. Empolderisation now protects the intrusion of sea water to agricultural areas but restricts the deposition of sediments to within the channels, thus reducing the drainage capacity of the rivers and channels, causing drainage congestion.

Soil is regarded as waterlogged when it is nearly saturated with water much of the time such that its air phase is restricted and anaerobic conditions prevail. In agriculture, various crops need air (specifically, oxygen) to a greater or lesser depth in the soil. Waterlogging of the soil stops air getting in. How near the water table must be to the surface for the ground to be classed as waterlogged, varies with the purpose in view. A crop's demand for freedom from waterlogging may vary between seasons of the year.

A livelihood is a way of making a living. It comprises capabilities, skills, assets (including material and social resources), and activities that households put together to produce food, meet basic needs, earn income, or establish a means of living in any other way.

Typically undesirable increase in concentration and deposition of water-borne silt particles in a body of water.

Water Management Improvement Project (WB-funded)

Coastal Embankment Improvement Project

A culvert is a structure that allows water to flow beneath a road, railroad, trail, or similar obstruction from one side to the other.

the adjustment of gates in water management infrastructure to control hydraulic conditions (water

levels and discharges) in a water management system.

Return on Investment

The practice of admitting (fresh or saline) water for irrigation (or shrimp production) through regulators or inlets.

A vertical gate to control the flow of water; also referred to as 'regulator'

Sedimentation is the process by which fine particles of silt and clay suspended in river water settle out, for example when there is a drop in velocity.

Retrieved from

"https://www.bluegoldwiki.com/index.php?title=Summary_of_Section_C:_Water_Infrastructure&oldid=6529"

Namespaces

- [Page](#)
- [Discussion](#)

Variants

This page was last edited on 19 December 2021, at 11:26.

Blue Gold Program Wiki

The wiki version of the Lessons Learnt Report of the Blue Gold program, documents the experiences of a technical assistance (TA) team working in a development project implemented by the Bangladesh Water Development Board (BWDB) and the Department of Agricultural Extension (DAE) over an eight+ year period from March 2013 to December 2021. The wiki lessons learnt report (LLR) is intended to complement the BWDB and DAE project completion reports (PCRs), with the aim of recording lessons learnt for use in the design and implementation of future interventions in the coastal zone.

- [Privacy policy](#)
- [About Blue Gold Program Wiki](#)
- [Disclaimers](#)

Developed and maintained by Big Blue Communications for Blue Gold Program



[Blue Gold Program Wiki](#)